反压高温蒸煮锅

ANTI-PRESSURE HIGH TEMPERATURE STEAM POT

双 哈 ®

FY50

性能特点：

- 不锈钢材质制成，经久耐用；
- 控制面板的斜面设计，便于观察操作；
- 微电脑程序控制加热和保温计时过程；
- LED数码管和指示灯，动态显示设备运行状态；
- 电脑板具有PID功能，通过自整定修正加热参数，可以防止冲温，控温精度达到±0.5℃以内；
- 低水位自动补水功能，且有声光报警系统，补完水自动恢复加热；
- 重力排汽法设计，腔内纯蒸汽环境，效果可靠；
- 径向自胀式硅橡胶密封圈，密封效果好，使用寿命长；
- 温度超过设定值2℃，自动停止加热，同时声光报警；
- 超压到0.23MPa安全阀自动泄放蒸汽，保护设备；
- 提供防爆袋的反压接口；
- 冷水喷淋装置可以加速内部物体冷却速度，从135℃降温至室温只需8~10min；
- 空气反压辅助装置可供用户选配；
- 改善传统高温消毒过程中包装袋易破裂的缺点；
- 放水阀可以排放桶内浓缩水，防止结垢；
- 带刹车的万向脚轮移位轻捷，定位方便；
- 浸入式电加热管，热效率高。
- **本产品属于简单压力容器，按规定无需办理使用证即可使用。**



FY50

Performance and characteristic:

- Made from stainless steel,durable used;
- Inclined control panel; easy operation;
- Mirco-computer can contrl heating,heat preservation;
- LED digital tube and light, indicate the status of equipment;
- PID temperature-controlled function, can modify the control indicate to prevent the temperature,precision of temperature controlled:±0.5℃;
- Adding water when water lack, when reach the normal water level, continue heating when adding water;
- Gravity exhaust design, effect stable;
- The airproof ring made of silicon rubber is not only durable but also with better result;
- Over temperature(set temperature +2℃) stop heating and alarm;
- Over pressure to 0.23Mpa, safety valve open and push the steam;
- Offer interface for explosion proof bag;
- Water spraying can be fast for cooling process, it only take 0-10min to make temperature from 135% to room temperature;
- Anti-air pressure auxiliary device can be choosed;
- Imrpove the disadvantage for breaking bag during sterilized process;
- Drain valve can push the water in container, prevent bilge;
- Muti-direction of wheel with brake,easy moving and position;
- Immerge electric heating tube, heat efficiency is better.

主要技术参数(MainTechnicalData)：

型号 Model	工作电源 Electric Supply	功率(kW) Power	容积(L) Cubage	补水压力(Mpa) Operating pressure	工作压力(Mpa) Operating pressure	工作温度(℃) Operating temperature	保温时间 Soaking time	器内温差(℃) In instrument temperature difference	内桶尺寸(cm) Barrel size	外形尺寸(cm) Product size	包装尺寸(木)(cm) Product size (Wooden)	毛重(kg) gross weight	净重(kg) Net weight
FY50	AC 220V /50Hz	3.8	50	≥0.2≤0.3	随温度 Along with temperature change	室温 Indoor temperature +5～135自选 Optional	1～99.99 (分钟或小时) Minute or hour	<1	∅40×50	55×66×100	76×61×122	100	75

上海三申医疗器械有限公司
SHANGHAI SANSHEN MEDICAL INSTRUMENT CO.,LTD.