



手提式不锈钢压力蒸汽灭菌器

STAINLESS STEEL HANDLE STEAM PRESSURE DISINFECTOR

YX280/15、YX280/20(定时数控TIMING CONTROL)



YX280/15 YX280/20

(定时数控)

性能特点:

- 灭菌器按YY0504-2016标准, 具有联锁装置安全效果
- 旋转式90度开盖手柄, 操作时特别方便、安全
- 可以按需设定灭菌温度, 工作温度设定范围: 室温+5~126℃
- 可以按需设定灭菌保温时间, 保温时间设定范围: 1~99min
- 灭菌器盖设有安全阀, 能有效防止超压引起的安全隐患
- 灭菌器盖设有冷空气排放阀(放汽阀), 可以在加热开始时排放器内的冷空气
- 双刻度线压力表指针指示清晰, 观察方便, 性能可靠
- 灭菌器控制面板在合适的工作高度范围内所有的指示非常清晰, 操作十分方便
- 灭菌过程的温度和时间由LED数码管按程序分段显示
- 操作面板上的LED指示灯按操作需要和运行状态点亮显示
- 灭菌器具有“自整定”功能
- 灭菌器具有低水位停止继续加热功能
- 灭菌器在低水位、保温结束终止程序时有蜂鸣器报警提示的功能
- 灭菌器设有运行控制开关, 防止设备通电后加热管立即开始工作的弊病
- 灭菌器工作过程(升压后)无蒸汽排放污染环境, 无噪声产生干扰工作
- 本产品采用SUS304优质不锈钢制成。具有在正常条件下工作足够的安全强度
- 灭菌器的径向自胀浮盖密封结构密封效果优异, 并已获得国家专利, 密封圈采用硅橡胶制成
- 灭菌器底部设有座圈和放水龙头, 产品放置时稳定性好, 排放浓缩水方便
- 浸入式电加热管热效率高, 不锈钢外管坚固耐用

Performance and characteristic:

- ▶ According to standard yy0504-2016, sterilizer has safety effect of interlocking device
- ▶ 90 degree rotary open lid handle, convenient and safe operation
- ▶ Can be set as required sterilization temperature, working temperature range: room temperature + 5~126℃
- ▶ Can be set as required sterilization time of heat preservation, heat preservation time setting range: 1~99min
- ▶ Disinfectant cover is provided with safety valve, can effectively prevent overpressure caused by the unsafe hidden danger
- ▶ Disinfectant cover is provided with a cold air discharge valve (steam valve), in the start of heating the cold air in the discharge device
- ▶ Double groove gauge clear indication, convenient observation, reliable performance
- ▶ Disinfectant control panel at a proper working height within all the instructions are very clear, the operation is very convenient
- ▶ During the sterilization temperature and time through the LED digital tube display setting program
- ▶ The operation panel on the LED indicator according to the operation needs and the running state of light display
- ▶ Disinfectant has the "tuning" function
- ▶ Disinfectant having a low water to stop heating function
- ▶ Disinfectant in low water level, insulation end termination programs have a buzzer alarm function
- ▶ The Disinfectant is provided with an operating control switch, to prevent the equipment after the electricity heating tube to start work immediately malady
- ▶ Disinfectant working process (pressure) without steam discharge pollution, no noise interference
- ▶ This product uses the high quality stainless steel SUS304. Having to work under normal conditions adequate safety strength
- ▶ Disinfectant radial self expanding floating cover sealing structure of excellent sealing effect, and has obtained national patent, the sealing ring is made of silicon rubber
- ▶ The Disinfectant is provided at the bottom of base ring and discharge water, down products of good stability, convenient to discharge condensed water
- ▶ Immersion type electric heating pipe thermal efficiency is high, durable stainless steel tube

主要技术参数(Main Technical Data):

型号 Model	工作电源 Electric Supply	功率(kW) Power	时间设定 Time setting	温度设定(℃) Temperature setting	工作压力 (MPa)	有效容积(L) Volume	储物桶尺寸 (cm) Product size	包装尺寸(cm) Product size	毛重(kg) gross weight	净重(kg) Net weight
YX280/15 定时数控	AC 220V /50Hz	2	1~99' Usually is the closure	室温+5~126 Indoor temperature	随温度 Along with temperature change	15	28×21	42×42×65	12	10
YX280/20 定时数控	AC 220V /50Hz	2	1~99' Usually is the closure	室温+5~126 Indoor temperature	随温度 Along with temperature change	20	28×31	42×42×74	14	12