双 哈 ®

立式压力蒸汽灭菌器

STAINLESS STEEL VERTICAL STEAM PRESSURE DISINFECTOR

YM50L/YM75L/YM100L (触摸屏控制型、内循环Touch Screen Intelligence、Internal recycling)



YM50L YM75L YM100L

性能特点：

- 不锈钢材质，径向自胀式密封圈；
- 拨杆弹盖结构，开盖自动弹起，上盖有耐高温防烫保护结构；
- 上置触摸液晶显示屏，便于操作观察；
- 微电脑自定义程序设定，满足不同灭菌需求；
- 大屏幕直观显示灭菌过程，显示设备运行状态；
- 压力安全联锁装置，有压状态下上盖无法打开；
- 缺水自动补水功能，补水完毕，自动恢复加热；
- 具有声光报警系统，缺水、灭菌结束蜂鸣提示；
- 超温自动控制和安全阀超压自泄双重保护；
- 超静音设计，自带废气处理系统，蒸汽内循环；
- 灭菌过程中冷空气自动排出功能；
- 灭菌结束有自动排汽或手动排汽供选择；
- 实时打印功能，记录灭菌过程数据；并有USB端口，可以将灭菌记录拷贝U盘保存；
- 具有查看本机使用次数记录功能
- 内设TT/PT温度、压力测试验证接口
- 灭菌器压力容器设计压力0.25Mpa、工作压力0.23Mpa，安全阀泄放压力0.24Mpa；
- 温度可在105-136℃范围内任意设置
- 带刹车的万向脚轮,移位轻捷，定向方便；
- 浸入式电加热管，热效率高。
- **本产品属于简单压力容器，按规定无需办理使用证即可使用。**

Performance and characteristic:

- Stainless steel material, radial self-expanding sealing ring;
- The lever cover structure, the cover automatically bounces, and the upper cover has a high temperature and anti-scalding protection structure;
- The upper touch LCD screen is convenient for operation and observation;
- Microcomputer custom program settings to meet different sterilization needs;
- The large screen visually displays the sterilization process and displays the operating status of the device;
- Pressure safety interlock device, the upper cover cannot be opened under pressure;
- Water shortage automatic water replenishment function, after the water is replenished, the heating is automatically restored;
- With sound and light alarm system, short of water, sterilization end beep prompt;
- Over-temperature automatic control and safety valve overpressure and self-discharge double protection;
- Ultra-quiet design, self-contained exhaust gas treatment system, steam internal circulation;
- Automatic cold air discharge during sterilization;
- At the end of sterilization, there is automatic steam exhaust or manual steam exhaust for selection;
- Real-time printing function, record the sterilization process data; and have a
- USB port, you can save the sterilization record copy in USB disk;
- Have the ability to view the usage count of this machine
- Built-in TT/PT temperature and pressure test verification interface
- The design pressure of the sterilizer pressure vessel is 0.25Mpa, the working pressure is 0.23Mpa, and the relief pressure of the safety valve is 0.24Mpa;
- The temperature can be set arbitrarily in the range of 105-136 °C;
- Universal casters with brakes, light displacement and convenient orientation;
- Immersion electric heating tube with high thermal efficiency.

主要技术参数(MainTechnicalData)：

型号 Model	工作电源 Electric Supply	功率(Kw) Power	容积(L) Cubage	补水水压 (Mpa) Operating pressure	工作温度(℃) Operating temperature	保温时间 Soaking time	控温精度(℃) Temperature control accuracy	网篮尺寸(cm)/个数 Basket size (cm) / number	外形尺寸(cm) Product size	包装尺寸(cm) Product size (wooden)	毛重(kg) gross weight	净重(kg) Net weight
YM50L	AC220V /50HZ	3	50	≥0.2≤0.3	≤136	≤999min	±0.5	Φ38×18/2	70×51×82	73×61×100	110	90
YM75L		3	75					Φ38×25/2	70×51×93	73×61×110	115	95
YM100L		4	100					Φ38×18/3	70×51×104	73×61×120	125	100